

# Verifone UX100



### Processor

32-bit RISC



### Display

2.5" (128 x64), white backlit



### Keypad

10 + 6 keypad; 10 numeric, 4 colored-embossed function; 2 navigation keys; durability of 2,000,000 presses each



### Connectivity

USB B 2.0 full speed



### Security

PCI PTS 5.X-approved



### Environmental

-20°C to 70°C (-4°F to 158°F) operating temperature, -25°C to 70°C (-13°F to 158°F) 10% to 90% relative humidity, non-condensing



### Physical

UX 100: 142 mm L x108 mm W x26 mm H (5.59 in. L x4.25 in. W x1.02 in. H)

UX110: 101mm L x108mm W x26mm H (3.98 in. L x4.25 in. W x1.02 in. H)



### Mechanics (cutout)

UX100: 120 mm x82 mm (4.72 in. x3.23 in.)

UX110: 75mm x75mm (2.95 in. x2.95 in.)

## Take your unattended transactions to the next level with the UX100 and UX110 PIN pads.

These secure modules work with other UX devices to meet self-service demands indoors and out. Featuring an LCD screen that helps guide the customer experience, the UX100 offers high performance and excellent durability. And with its weatherproof construction, the UX110 is ideal for off-street parking meters, petroleum pumps, ticketing machines and more. Pair them with the UX300 card reader to optimize your transaction functionality. Simple to integrate, the UX Series features flexible configuration settings with easy, single-cable connection between devices.