














Verifone UX300



- 
Processor
 400 MHz, ARM11 32-bit RISC processor
- 
Display
 Optional with UX 100
- 
Physical
 150mm L x 96mm W x 71mm H
 (5.91 in. L x 3.78 in. W x 2.8 in. H)
- 
Connectivity
 100Mbit LAN, USB-Slave, RS232 Optional MDB, RS485, GPRS, PSTN, ISDN, 4X USB-Master, 2nd LAN
- 
Contactless
 Optional with UX 400
- 
Security
 PCI PTS 4.x approved
- 
Memory
 384MB (256MB Flash, 128MB SDRAM)
- 
Operating System
 Embedded Linux with Verifone security enhancements
- 
Card Readers
 Hybrid, triple track MSR, landed smart card, EMVCo approved
- 
Power
 12VDC power supply, optional 9VDC/42VDC, 2 power-saving modes
- 
Mechanics (cutout)
 73.2mm x 61.2mm (2.88 in. x 2.41 in.)
- 
Environmental
 -20° to 70° C (-4° to 158° F) operating temperature, -25° to 70° C (-13° to 158° F) storage temperature, 10% to 90% relative humidity, non-condensing
- 
Other Standard Features
 2 SAM slots, 3 control LEDs, buzzer, real-time clock

Consider the UX300 card reader/controller your new, most dependable employee.

This versatile, self-service solution provides secure and reliable transactions for vending machines, public transportation and other unattended, high-transaction-volume environments. Programmed to read most bank cards, chip cards and mag-stripe cards, the UX300 hybrid card reader works alone or in combination with UX Series PIN pad and NFC-reader options to add more functionality to your self-service environments.